


317G COMPACT TRACK LOADER SPECIFICATIONS

Engine		317G	
Manufacturer and Model	Yanmar 4TNV86CHT	Displacement	2.1 L (128 cu. in.)
Non-Road Emission Standard	EPA Final Tier 4/EU Stage IV	Rated Engine Speed	2,600 rpm
Cylinders	4	Torque Rise	16% at 1,690 rpm
Net Power (SAE J1349 / ISO 9249)	45.6 kW (61 hp) at 2,600 rpm	Aspiration	Turbocharged
Gross Rated Power (ISO 14396)	48.5 kW (65 hp) at 2,600 rpm	Air Cleaner	Dry dual element
Peak Torque	207 Nm (153 ft.-lb.) at 1,690 rpm		
Cooling			
Fan Type	Direct belt drive		
Powertrain			
Pump	Axial-piston hydrostatic	Gearbox	High-drive direct-drive motor
Motors	Axial-piston hydrostatic	Brakes	Integral, automatic, spring-applied, hydraulically released, wet-disc park brake
Single Speed	11.3 km/h (7.0 mph)		
Undercarriage			
Rubber Tracks	Smooth-ride long-life rubber with steel inserts	Track Rollers (per side)	4 triple-flange smooth-ride all-steel rollers
Ground Pressure		Track Idlers (per side)	1 double-flange and 1 single-flange smooth-ride all-steel rollers
With Standard 320-mm (12.6 in.) Track	38 kPa (5.5 psi)	Bearings/Seals (rollers/idlers)	Heavy-duty journal bearings and metal face seals
With Optional 400-mm (15.8 in.) Wide Track	31 kPa (4.5 psi)	Tractive Effort	3632 kgf (8,000 lbf)
Hydraulics			
Type	3-spool open-center valve	Hydraulic Horsepower (calculated)	25 kW (33 hp)
Pump Flow, Standard	63 L/m (17 gpm)	Auxiliary Hydraulics	Standard connect-under-pressure with flat-faced couplers
System Pressure at Couplers	23 787 kPa (3,450 psi)		
Cylinders			
Type	John Deere heat-treated, chrome-plated, polished cylinder rods, hardened steel (replaceable bushings) pivot pins		
Electrical			
Voltage	12 volt		
Capacity			
Battery	750 CCA standard / 925 CCA with optional cold weather start package		
Reserve	180 min.		
Alternator Rating	70 amp with no air conditioning (A/C) / 90 amp with A/C		
Lights			
Standard	Halogen: 2 front and 1 rear		
Deluxe (optional)	LED: 2 front, 2 side, and 1 rear		
Operator's Station			
ROPS (ISO 3471) / FOPS (ISO 3449) structure with quick pivot standard; keyless-start option with sealed-switch module			
Serviceability			
Refill Capacities			
Fuel Tank	71 L (19 gal.)		
Cooling System	12 L (12.7 qt.)		
Operating Weights			
With Standard 320-mm (12.6 in.) Track	3824 kg (8,423 lb.)		
With Optional 400-mm (15.8 in.) Wide Track	3942 kg (8,683 lb.)		
Machine Dimensions			
A Length Without Bucket	2.63 m (103.0 in.) (8 ft. 7 in.)		
B Length			
With Foundry Bucket	3.24 m (127.6 in.) (10 ft. 8 in.)		
With Construction Bucket	3.49 m (137.4 in.) (11 ft. 5 in.)		
C Width Without Bucket			
With Standard 320-mm (12.6 in.) Track	1.65 m (65.1 in.) (5 ft. 5 in.)		
With Optional 400-mm (15.8 in.) Track	1.82 m (71.5 in.) (5 ft. 11 in.)		
D Height to Top of ROPS	1.99 m (78.5 in.) (6 ft. 6 in.)		
E Height to Hinge Pin	3.07 m (121.0 in.) (10 ft. 1 in.)		
F Dump Height			
With Foundry Bucket	2.43 m (95.6 in.) (8 ft. 0 in.)		
With Construction Bucket	2.26 m (89.0 in.) (7 ft. 5 in.)		
G Dump Reach			
With Foundry Bucket	0.79 m (31.0 in.)		
With Construction Bucket With Edge	0.98 m (38.6 in.) (3 ft. 3 in.)		
H Ground Clearance	0.21 m (8.3 in.)		
I Angle of Departure	32.3 deg.		
J Front Turn Radius With Foundry Bucket	1.97 m (77.7 in.) (6 ft. 6 in.)		
K Dump Angle (full lift height)	42 deg.		
L Bucket Rollback (ground level)	30 deg.		



While general information, pictures, and descriptions are provided, some illustrations and text may include product options and accessories NOT AVAILABLE in all regions, and in some countries products and accessories may require modifications or additions to ensure compliance with the local regulations of those countries.